

PRECAUTIONARY STATEMENTS

FIRSTAID

Have the product container or label with you when calling a poison control center or going for treatment.

- If swallowed:** Call a poison control center or a doctor immediately for treatment advice. Do not induce vomiting unless told to by a poison control center or doctor. Do not give anything by mouth to an unconscious person.
- If in eyes:** Hold eyes open and rinse slowly and gently with water for 15-20 minutes. Remove contact lenses, if present after the first 15 minutes, then continue rinsing. Call a poison control center or doctor for treatment advice.
- If on skin:** Remove contaminated clothing. Rinse skin immediately with soap and plenty of water for 15-20 minutes. Call poison control center or doctor for treatment advice.
- If inhaled:** Move person to fresh air. If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably mouth-to-mouth if possible. Call a poison control center or doctor for further treatment advice.

HAZARDS TO HUMANS AND DOMESTIC ANIMALS

CAUTION: Harmful if absorbed through the skin. Avoid contact with skin, eyes or clothing. May cause eye or skin irritation. Prolonged or frequently repeated skin contact may cause allergic reactions in some individuals. Harmful if inhaled. Avoid breathing vapor. Wash thoroughly with soap and water after handling. Do not use or store near heat or open flame.

PERSONAL PROTECTIVE EQUIPMENT

All pesticide handlers (loaders and applicators) must wear full length coveralls worn over a minimum of short-sleeved shirt and short pants, socks ,

USER SAFETY REQUIREMENTS

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables are available, use detergent and hot water. Keep and wash PPE separately from other laundry.

ENVIRONMENTAL HAZARDS

Do not apply directly to water, or to areas where surface water is present or to intertidal areas below the mean water mark. Do not contaminate water when disposing of equipment, washwater or rinsate.

SPILL PROCEDURES

Remove source of spill. Use absorbent materials to clean up liquid spills. Put absorbed liquid in waste disposal container and flush contaminated surfaces in water. Dispose of according to local and regional authority requirements. This product is biodegradable.

STORAGE AND DISPOSAL

Do not contaminate water, food or feed by storage and disposal.

Pesticide Storage: Store in original container in a cool, dry

Pesticide Disposal: Wastes resulting from the use of this product may be disposed on site or at an approved waste disposal facility.

Container Disposal: Nonrefillable container. Do not reuse or refill this container. Triple rinse (or equivalent) promptly after use. Offer for recycling if available, or puncture and dispose of in a sanitary landfill, or by other approved State and local procedures.

DIRECTIONS FOR USE

IT IS A VIOLATION OF FEDERAL LAW TO USE THIS PRODUCT IN A MANNER INCONSISTENT WITH ITS LABELING FOR USE ON WOOD STRUCTURES AND/OR WOOD OBJECTS

Structural Drywood Termite Infestation: Applicator must locate termite galleries. Visual signs of infestation such as frass or pellets, blistered wood, "kick-out holes" and presence of live insects can be used to locate nests and galleries. Fiber optic equipment or listening devices can also be used. Tapping on wood with screwdriver and listening for different sounds that would indicate variations in wood density may help locate galleries.

Application Equipment: Apply **XT-2000 ORANGE OIL PLUS** using brass or stainless steel injector with brass or stainless steel nozzles, pressurized to 10-15 psi at the nozzle.

Wood Injection: Drill 7/64" holes into "kick-outs" to intersect galleries within infested wood. Avoid electrical wiring and plumbing when drilling. Do not drill completely through wood. Use a "w" pattern at 3"-5" intervals to ensure coverage and penetration of **XT-2000 ORANGE OIL PLUS**. Drill holes on opposite sides of 4" x 10" or larger beams to effectively penetrate galleries. Inject for up to one minute. Avoid splash back or runoff from excessive or prolonged use. Plug holes after treatment with wood filler or other non-wood material. Apply at a rate not to exceed 0.22 gallons (28 fl. oz) per cubic foot of wood.

Retreatment: Do not apply again to the same area within one year.

Wood Boring Beetle Infestation: Applicator must locate beetle infestation. Topically apply **XT-2000 ORANGE OIL PLUS** at a rate of 1 gallon per

Retreatment: Do not apply again to the same area within one year

Structural Carpenter Ant Infestation: This product will only kill foraging carpenter ants present at the time of application. Applicator must locate ant infestation and inject 1 oz. of **XT-2000 Orange Oil Plus** into wall void framing using a brass or stainless injector with brass or stainless nozzles, pressurized to 10-15 psi at the nozzle. Patch and seal area after treatment.

Retreatment: Do not apply again to the same area within one year.

WARRANTY

To the extent consistent with applicable law, XT-2000, Inc. warrants that this product conforms to its label description and is reasonably fit for the purposes stated on the label, when used in accordance with the directions and instructions specified on the label under normal conditions of use. To the extent consistent with applicable law, XT-2000, Inc. does not make, and does not authorize any agent or representative to make other warranties, express or implied, including, but not limited to, warranties of merchantability or fitness for the intended purpose. To the extent consistent with applicable law, XT-2000, Inc. shall not be liable for consequential damages for any injury or liability due to user failure to follow label instructions.